

ISUZU

**ELF**  
**NLR**  
**MICROBUS**

**BANYAK PENUMPANGNYA**  
**PASTI UNTUNGNYA**



Engine 4HG1-T



Engine 4JB1-TC



3,360 mm

Long Wheel Base



New Front Axle



New Head Unit



Acceleration



Hexa Pod Cabin

\*Khusus untuk NLR55 LBx & NLR71 BL

## SPESIFIKASI TEKNIS

DIMENSI / DIMENSION		NLR 55B	NLR 55Bx	NLR 55B Lx	NLR 71B L
Panjang / Overall Length (OAL)	mm	4,870	4,870	6,170	6,170
Lebar / Overall Width (OW)	mm	1,835	1,835	1,835	1,835
Tinggi / Overall Height (OH)	mm	2,170	2,170	2,170	2,200
Jarak Sumbu / Wheelbase (WB)	mm	2,490	2,490	3,360	3,360
Julur Depan / Front Overhang (FOH)	mm	1,110	1,110	1,110	1,110
Julur Belakang / Rear Overhang (ROH)	mm	1,270	1,270	1,700	1,700
Jarak Terendah Ke Tanah / Minimum Clearance (HH)	mm	190	190	190	190
Jejak Depan / Front Tread (AW)	mm	1,490	1,490	1,490	1,490
Jejak Belakang / Rear Tread (CW)	mm	1,410	1,410	1,410	1,410
Cabin to End (CE)	mm				

MESIN / ENGINE		4JB1-TC	4HG1-T
Model / Model		4JB1-TC	4HG1-T
Type / Type		Direct Injection, 4 Cylinder, VE, Turbo intercooler, OHV	Direct Injection, 4 In-line, Turbo, SOHC
Diameter X Langkah/ Bore X Stroke	mm	93 x 102	115 x 110
Isi Silinder / Piston Displacement	cc	2,771	4,570
Tenaga Maksimum / Maximum Power	PS/rpm	100 / 3,400	125 / 2,900
Torsi Maksimum / Maximum Torque	Kgm/rpm	22.5 / 2,000 - 3,200	35 / 1,200 - 2,200

TRANSMISI / TRANSMISSION		MSB55	MSB5M	MSB5M	MY5T
Model / Model		MSB55	MSB5M	MSB5M	MY5T
Perbandingan Gigi / Gear Ratio					
1st		5.016	5.594	5.594	5.315
2nd		2.672	2.814	2.814	3.053
3rd		1.585	1.660	1.660	1.655
4th		1.000	1.000	1.000	1.000
5th		0.770	0.794	0.794	0.721
Rev		4.783	5.334	5.334	5.068
Perbandingan Gigi Terakhir / Final Gear Ratio		4.875	5.857	5.857	4.300

BERAT / WEIGHT					
Berat Total Kendaraan / Gross Vehicle Weight (GVW)	kg	5,100	5,100	5,100	5,100
Berat Kosong Kendaraan / Curb Weight	kg	1,490	1,590	1,680	1,910

REM / BRAKE	NLR 55B	NLR 55Bx	NLR 55B Lx	NLR 71B L
Rem Kaki / Service Brake	Hydraulic, saluran ganda dengan vacuum booster			
Rem Tangan / Hand Brake	Mekanisme expanding di transmisi belakang			
Sistem Pengereman Gas Buang / Exhaust Brake	Tidak Ada	Ada	Ada	Ada

KAPASITAS GARDAN / AXLE CAPACITY				
Depan / Front	kg		2,550	
Belakang / Rear	kg		2,550	

RODA / TYRE				
Ban depan / Front Tyre			Single, 225/75/R16	
Ban belakang / Rear Tyre			Single, 225/75/R16	
Velg / Disc Wheel Size			16 X 7.00	

SUSPENSI / SUSPENSION				
Depan / Front			Semi elliptical laminated leaf spring dengan shock absorber berdaya ganda	
Belakang / Rear			Semi elliptical laminated leaf spring dengan shock absorber berdaya ganda	

LAIN-LAIN / OTHERS					
Kapasitas Tangki / Fuel Tank Capacity	ltr	75	75	100	100
Radius Putar Minimum / Minimum Turning Radius	m	5.1	5.7	7.4	7.1
Daya Tanjak Maksimum / Maximum Gradeability	%	22	29	29	38
Kecepatan Maksimum / Maximum Speed	km/h	102	108	108	125
Aki / Accu	V-Ah	12-60	12-60	12-60	12-52 x 2
Alternator	V-A	12-60	12-60	12-60	24-60
Power Steering		Ada	Ada	Ada	Ada
Tilt & Telescopic Steering		Ada	Ada	Ada	Ada
Kamera Mundur / Reverse Parking Camera		Ada	Ada	Ada	Ada
DVD, CD, MP3, USB, Aux In, Radio, SD Card		Ada	Ada	Ada	Ada
Retractable Seat Belt		Ada	Ada	Ada	Ada
Fan Blower		Ada	Ada	Ada	Ada

\* Untuk meningkatkan mutu dan penyesuaian dengan perkembangan teknologi, spesifikasi dapat berubah sewaktu-waktu tanpa pemberitahuan.  
\*\* Ilustrasi merupakan contoh sebagian aplikasi di lapangan.

## MESIN



### EFISIEN ENGINE 100 PS

Menggunakan mesin 4JB1-TC yang hemat bahan bakar namun tetap bertenaga untuk mendukung segala peruntukkan operasional usaha serta telah memenuhi standar Euro 2.



### TANGGUH ENGINE 125 PS

Performa mesin 4HG1-T telah teruji bertenaga untuk mendukung segala pengangkutan sekaligus perkasa melibas jalanan datar hingga tanjakan. Telah memenuhi standar Euro 2.

Agen Pemegang Merek & Distributor :

**PT ISUZU ASTRA MOTOR INDONESIA**

www.isuzu-astra.com